

120VAC IC RATED MINI-DIMMABLE AND ADJUSTABLE LED DOWNLIGHT

GM Lighting®

Project Name	Type
Catalog #	Date

PRODUCT OVERVIEW

GM Lighting's 120VAC 6W Mini LED Adjustable Shallow Recessed Downlight packs a lot of performance in a compact, easy to install dimmable luminaire. 3-3/4" optional white only trim ring is included with each fixture.



FEATURES

- 120VAC
- 3000K
- ELV Dimming
- 3-1/4" dia. x 3-3/4" recess depth
- 15° adjustable gimbal
- 90+ CRI
- Up to 500 lumens
- 24°, 38°, 55° beam spreads
- 5 year warranty

SPECIFICATIONS

- Mini-recessed extremely shallow mount with optional trim ring included.
- 120V operation, remote power supply not required.
- IC rated
- Approved for damp location
- Glass lens
- Improved heat sink
- 15° adjustability
- Dimmable with standard dimmer

ELECTRICAL

- 6W
- 120V

OPTICS

- 3000K
- Up to 500 lumens
- 90+ CRI

WARRANTY

- 5-year warranty



ORDERING INFORMATION

Example: GMR6-120V-IC-SP-W

Catalog No.	Dimensions	Watts	Beam Spread	Lumens	CRI	Color Temp	Finish
GMR6-120V-IC-SP-W	3-1/4" Dia. x 3-3/4" Depth	6W	24°	500	90+	3000K	W
GMR6-120V-IC-FL-W	3-1/4" Dia. x 3-3/4" Depth	6W	38°	455	90+	3000K	W
GMR6-120V-IC-WFL-W	3-1/4" Dia. x 3-3/4" Depth	6W	55°	467	90+	3000K	W
GMR6-120V-IC-SP-B	3-1/4" Dia. x 3-3/4" Depth	6W	24°	500	90+	3000K	B
GMR6-120V-IC-FL-B	3-1/4" Dia. x 3-3/4" Depth	6W	38°	455	90+	3000K	B
GMR6-120V-IC-WFL-B	3-1/4" Dia. x 3-3/4" Depth	6W	55°	467	90+	3000K	B
GMR6-120V-IC-SP-BA	3-1/4" Dia. x 3-3/4" Depth	6W	24°	500	90+	3000K	BA
GMR6-120V-IC-FL-BA	3-1/4" Dia. x 3-3/4" Depth	6W	38°	455	90+	3000K	BA
GMR6-120V-IC-WFL-BA	3-1/4" Dia. x 3-3/4" Depth	6W	55°	467	90+	3000K	BA

ACCESSORIES

Example: OTR-WH

Catalog No.	Description
OTR	3-3/4" trim ring - White, Black, Brushed Aluminum

Recommended Dimmers: Lutron PD-6WCL-WH-R, Lutron Diva DVLV-600P-WH, Lutron Diva DVELV-300P, Leviton R62-6674-POW, GM Lighting SHWD

Note: Ambient operating temp range -4F to 104 F. Do not install in an environment that is outside of the product's listed ambient temp.