

ST Series**Sunlite F21T5/830 21-Watt T5 Linear
Fluorescent Light Bulb Mini Bi Pin Base,
3000K, 40-Pack**

T5 High Performance Straight Tube

DESCRIPTION:

Sunlite fluorescent lamps are very popular for use in office and other lighting applications. The characteristics of fluorescent lamps vary type of lamp. Fluorescents lamps are used so widely due to their low operating costs and because they are efficient, last for years, and are high quality and rapid starting. Fluorescent lamps can cost significantly less to operate over their lifetime than incandescent lamps. Life ratings for fluorescent lamps range from 6,000 to 36,000 hours based on the industry standard of 3 burning hours per start. Also, rapid start and instant start lamps typically start within 1 second of being turned on. The High Performance and High Output versions also give you and even better efficacy and energy efficiency. Look for a higher CRI for improved light quality. Sunlite 30315-SU F21T5/830 3000K Color Temperature T5 Hight Performance Straight Tube Fluorescent 21 Watt lamp features a Mini Bi Pin base, provides a light output of 1900 lumens at a Color Rendering Index (CRI) of 82 and can last an average of 20000 hours.

FEATURES:

- The package length is 87.375 centimeters
- The package height is 11.176 centimeters
- The package width is 16.51 centimeters
- Package Weight : 8.25 pounds
-



SPECIFICATIONS:

General Characteristics

Bulb Shape	T5
Average Rated Hours	20000
Base	Miniature Bi-Pin (G5)
Average Life Span Years	18

Electrical Characteristics

Watts	21
--------------	----

Light Characteristics

Lumens Brightness	1900
Color Rendering Index CRI	82
Emitted Color	Warm White
Color Temperature Kelvin	3000K

Additional Features

Rohs Compliant	Yes
-----------------------	-----

Product Dimensions

Size	3 Foot
MOL (in)	34.00
Diameter (in)	0.625"
Item Dimension (in)	(W) 0.63 (H) 0.63 (D) 34
Package Dimension (in)	(W) 0.64 (H) 0.64 (D) 34
Package Weight (lb)	0.23

Product Data

Case Unit Rate	40
Pack Size	1
Item UPC	653703303154

