



LED InstantFit Lamps

10.5PL-C/T LED/26V-4000 IF 4P 10/1

Philips LED T8 InstantFit Lamps are an ideal energy saving choice for existing linear fluorescent fixtures.

Product data

General Information		Power Factor (Nom)	
Cap-Base	GX24Q-3 [GX24q-3]		0.9
Main Application	Industrial	Voltage (Nom)	120-277 V
Nominal Lifetime (Nom)	40000 h	Temperature	
Switching Cycle	50000X	T-Ambient (Max)	35 °C
B50L70	40000 h	T-Ambient (Min)	-20 °C
Light Technical		T-Storage (Max)	65 °C
Color Code	840 [CCT of 4000K]	T-Storage (Min)	-40 °C
Beam Angle (Nom)	120 °	T-Case Maximum (Nom)	77 °C
Luminous Flux (Nom)	1300 lm	Controls and Dimming	
Luminous Flux (Rated) (Nom)	1300 lm	Dimmable	No
Rated Beam Angle	120 °	Mechanical and Housing	
Correlated Color Temperature (Nom)	4000 K	Product Length	100 mm
Color Consistency	<6	Approval and Application	
Color Rendering Index (Nom)	82	Energy Saving Product	Yes
LLMF At End Of Nominal Lifetime (Nom)	70 %	Suitable For Accent Lighting	No
Operating and Electrical		Energy Efficiency Label (EEL)	A+
Input Frequency	50 to 60 Hz	Approval Marks	CE marking UL certificate RoHS compliance KEMA Keur certificate
Power (Rated) (Nom)	10.5 W	Energy Consumption kWh/1000 h	14.5 kWh
Lamp Current (Nom)	150 mA		
Starting Time (Nom)	0.5 s		
Warm Up Time To 60% Light (Nom)	instant full light s		

LED InstantFit Lamps

Product Data

Order product name	10.5PL-C/T LED/26V-4000 IF 4P 10/1
EAN/UPC - Product	046677458430
Order code	929001181404
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	10
Material Nr. (12NC)	929001181404
Net Weight (Piece)	0.090 kg

Warnings and Safety

- Philips LED T8 InstantFit lamps will only operate properly on compatible instant-start ballasts. Please refer to the Philips LED T8 InstantFit Installation Guide, which can be obtained through your local Philips Sales Representative, or visit www.philips.com/tled

Dimensional drawing

Product	D1	D2	A1	A2	A3
10.5PL-C/T LED/26V-4000 IF 4P 10/1	24.3 mm	29 mm	99.9 mm	109.9 mm	125.5 mm

LEDtube 100mm 10.5W/840

Photometric data

LED InstantFit PL-C/T 100mm 10.5 W /840

