

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



UPC: 192552025546



Features and Benefits

Replaces traditional 175W Metal Halide
 Integral driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
 Rated for use in open and enclosed fixtures in dry, damp, or wet locations
 Full glass design provides omnidirectional output
 25,000-Hour lifespan

Technical Specifications

Performance

Product Type:

Filament HID Replacement

Description:

Classic filament style lamp adds a decorative aesthetic to any post top, bollard, or corridor application

Wattage Equivalency:

175W Metal Halide

Input Wattage:

36W

Lumens (Nominal):

6,000 Lm

Efficacy:

167 Lm/W

L70 Lifespan:

25,000-Hour LED lifespan based on IES LM-70 results

Electrical

Power Factor:

≥0.9

Input Voltage:

120-277V

Operating Frequency:

50/60Hz

Operating Temperature:

-4°F - 113°F (-20°C - 45°C)

Flicker:

<70%

Surge Protection:

4kV

LED Characteristics

Color Temperature:

5000K

Color Accuracy (CRI):

≥80 CRI

R9 Value:

High color performance with R9 no less than 0

Color Consistency:

<6-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Technical Specifications (continued)

Installation

Installation Method:

UL Type B

Installation Orientation:

Vertical

Construction

Base Type:

EX39

Bulb Shape:

ED28

Endcap Material:

Ceramic

Enclosure Material:

Glass

Lens Finish:

Clear

Compliance

Safety Listing:

UL Listed

Environment:

Suitable for use in dry, damp, and wet environments

Fixture Rating:

Suitable for use in enclosed fixtures

IP Rating:

Ingress protection rating of IP65 for dust and water

Energy Star Approved:

No.

There is no product category on Energy Star for this lamp to qualify under.

DLC Listed:

No, this product is not DLC Listed.

T20 Compliant:

Not compliant

California Title 24 JA8 Compliant:

Not compliant

California Energy Commission (CEC) Status:

Lawful for Sales in California

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Other

Compatible Products:

[SP10KV](#)

Surge Protector

[XFMR200-480-277](#)

Step Down Transformer 480V to 277V

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Note:

All values are typical (tolerance +/- 10%)

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	6	13.78	9.25	11.02
PALLET	13	47.24	39.37	23.62

Dimension

