

### Product Features:

- Smallest Form Factor in Mogul-Base Category
- Integrated 4kA/4kV Surge Protection
- Step-Down Thermal Management Protection
  - Wattage step-down circuit automatically prevents overheating due to high increases in ambient temperatures. Wattage returns to normal as temperatures decrease.
- Omni-directional
- Rated for Fully Enclosed Fixtures
- Wet Location Approved
- Special Adapter Transforms Base from E26 to E39
- Direct Retrofit for HID & CFL Fixtures

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Product Specifications:

Selectable Power: 12 Watts, 18 Watts, 27 Watts

Lamp Lumen Output: Up to 2,931 Lumens

Lamp Efficacy: Up to 106 (lm/W)

Selectable Kelvin: 3000K, 4000K, 5000K

Dimensions:

(E26) 2.36"Ø x 6.57"

(EX39) 2.36"Ø x 7.36"

CRI: >80

Input Voltage: 120–277 VAC

Life Span: 50,000 Hours

Beam Angle: 300°

Base Types:

S-M (E26 with E39 adapter)

EX39

Operating Temperature: -40°F~140°F(-40°C~60°C)

Power Factor: >0.9

Total Harmonic Distortion (THD): < 20%

### SELECTABLE WATTS

12W, 18W, or 27W



SELECTABLE KELVIN  
3000K, 4000K or 5000K

**EXCLUSIVE**  
E39–E26 Adapter Included



No Fans



No Noise



No Bugs



### Ordering Guide:

ESL	-	TYPE	-	SELECTABLE WATTAGE	-	GENERATION	-	SELECTABLE KELVIN	-	BASE
ESL	-	CL (CL) Corn Light	-	1227W 12 Watts, 18 Watts, 27 Watts	-	5 (5) 5th Generation	-	3050 3000K, 4000K, 5000K	-	vv (S-M) E26/ (EX39) EX39

### FIELD INSTALLED ACCESSORIES

ESL-SPD-300V-10KV	Hardwire surge protector, (100–300 VAC) maximum discharge current: 10kA
-------------------	---

### Catalog Data:

ITEM#	SELECTABLE WATTAGE	SELECTABLE KELVIN	MAX LUMEN OUTPUT	MAX EFFICACY (lm/w)	INPUT VOLTAGE	CASE QTY	DLC OPL
ESL-CL-0918W-53050-S-M	9W, 12W, 18W	3000K, 4000K, 5000K	2,143	123	120–277 VAC	16	S-1E8PLD
ESL-CL-0918W-53050-EX39	9W, 12W, 18W		2,143	123	120–277 VAC	16	N/A
ESL-CL-1227W-53050-S-M	12W, 18W, 27W	3000K, 4000K, 5000K	3,931	106	120–277 VAC	16	S-QLJ8VT
ESL-CL-1227W-53050-EX39	12W, 18W, 27W		3,931	106	120–277 VAC	16	N/A

\* 5000K Lumen and Efficacy data listed. See specification sheet for other kelvin information.

### Product Dimensions:

