

## Exit & Emergency

### Edgelit Exit Series

- LED Edgelit Aluminum Exit Sign
- Universal Red/Green Stencil Face
- Universal Single/Double Face
- Universal Mounting
- Universal Input Voltage
- Universal Chevron Indicators

### Specifications

#### Description

The Emergence Series Edgelit Exit Sign offers the most versatile code compliant solution for hallway, stairwell, and other Life Safety applications. The universal red/green legend, field-selectable single/double face, and universal ceiling/end/wall mounting includes universal applique chevron indicators as well as universal input voltage to provide the most field configurable edgelit exit sign on the market. The pivoting housing design makes it ideal to mount on ceilings or walls in surface, end or top mount configurations, indicating the path of egress for a minimum of 90 minutes after a power loss.

#### Electrical

- 120 / 277 VAC, 60Hz input
- Emergency test button and battery charging indicator
- Long-life maintenance free NiCad battery
- 24 hour recharge time
- Battery low voltage circuit protection
- Solid state transfer circuit


#### Certifications

- UL924 damp location listed
- NFPA 101 and NFPA 70
- CEC T20 compliant
- 10°C to 40°C operating temperature

#### Applications

- Commercial
- Retail
- Hospitality
- Office
- Medical

### EMERGENCE<sup>™</sup> SERIES



SLIDER SWITCH



#### Construction & Mounting

- Extruded aluminum housing with high grade replaceable acrylic panel
- Long life, high intensity LEDs
- Fully illuminated 6" legend with 3/4" stroke
- Field-selectable applique chevrons
- Suitable for ceiling, end and wall mount.
- Universal J-box mounting pattern on back plate
- Canopy included

#### Warranty

- 2 year full warranty

Exit & Emergency

## Edgelit Exit Series

### Ordering Logic

Product SKU	Product Code	Product Description
97104	EMG-EDG-AL-RG	Emergence Series, Aluminum Edgelit Exit, Universal Red/Green, Universal Single/Double Face, Universal Mounting

### Specifications Table

	EMG-EDG-AL-RG
Housing	Pivoting Extruded Aluminum
Mounting	Ceiling, End or Wall - Canopy Included
Panel	Snap-in/out Field Replaceable Clear Acrylic
Face	Universal Single/Double Face
Face Insert	Double-Face Mirror Insert Included
Legend	Uniformly illuminated 6" height, 3/4" Stroke
Chevrons	Field Selectable Applique
Letter Color	Field Selectable Red/Green
LED Life Expectancy	100,000 hours+
Input Voltage	120 / 277 VAC
Frequency	60Hz
Battery	Maintenance Free NiCad
Recharge	<24 hours
Recharge	90 minutes+
Remote Capacity	-
Output Voltage	-
Testing Function	Manual Test Button w/Charging Indicator
Protections	Low Voltage Disconnect Battery Protection
Operating Temperature	10°C to 40°C
Listings & Compliance	UL 924, CEC Title 20, NFPA 101 & NFPA 70
Environment	Damp Location Listed
Warranty*	2 Year

\*All life safety equipment, including emergency lighting for path of egress must be maintained, serviced, and tested in accordance with all National Fire Protection Association (NFPA) and local codes. Failure to perform the required maintenance, service, or testing could jeopardize the safety of occupants and will void all warranties.

### Dimensions

