

Features & Benefits

- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long Life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Utilizes shunted or unshunted G13 sockets
- 5-CCT Field-Adjustable: 27K/30K/35K/40K/50K
- Works in cold temperature applications
- Suitable for damp and dry locations
- Glass tube for superior optical performance
- -4° F to 113° F ambient operating temperture
- 5 Year Warranty



Commercial Grade LED T8 Lamp
Double End Input



Flex™
Internal Driver LED Lamp

Specification Data

Model No.	Length	Base type	Lamp Wattage	Input Voltage	CCT	Initial Lumens	CRI	Beam Angle	LPW	Power Factor	THD	Life (h)
L48T8/8F/12G-ID DE	48	G13	12	120-277	2700K	1600	82	200	133	0.9	<20%	50,000
					3000K	1600			133			
					3500K	1650			138			
					4000K	1800			150			
					5000K	1800			150			

Order Information

EXAMPLE: L48T8/8F/12G-ID DE

L

Manufacturer's Code

48

Normal Length
48 = 48"

T8

Lamp Shape
T8 = T8

8

CRI
8
=>80

F

5-CCT field-adjustable
27K/30K/35K/40K/50K

12 G

Wattage
12G-12W
Glass

-

ID

Internal Driver

DE

Double End Input

Wiring Diagram

