RDP SERIES RESIDENTIAL LIGHTING




RDPF6-ADJ-MCT5

LED TRIMS



LED retrofit trims have been designed to be a flexible lighting solution for retrofit and new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications.

Customer Name: Project Name: Note: Type:



7 1/2" x 3 1/4"

-eatures

- 6" Recessed Trim
- Multi CCT (Selectable Switch on the Back of the driver)
- Isolated Driver for Improved Thermal Management
- Can Rotate after Installation to Align

- 5-Year Warranty
- Composite Polycarbonate, White Finish
- Tilts to 45°

Technical Specifications

Electrical:

Voltage: 120V AC Output Voltage: 36VDC Power Factor: >0.90

Wattage: 11W Efficacy: 80LPW

Total Harmonic Distortion: ≤15 %

Lighting:

- Dimming: TRIAC Dimming (Using Standard TRIAC LED Dimmers)
- LED: Epistar Chip (COB) and Driver
- Can Rotate after Installation to Align
- Adjustable Lens & Tilts 45°
- Total Lumens: 880LM
- Color Temperatures: 2700K/ 3000K/ 3500K/ 4000K/ 5000K
- Multi CCT (Selectable Switch on the Back of the driver)
- Color Rendering Index: CRI ≥ 90
- Rated life: 50,000 hrs

Mechanical:

- Composite Polycarbonate, White Finish
- Type IC (Insulation Contact), Suitable For Direct Contact With Insulation
- Includes 8" Medium Base E-26 Screw-in Adapter That Fits any Standard Incandescent Down-light
- White Translucent Acrylic Lens
- Maximum Ambient Temperature: 104°F
- Fits in Standard 6" Recessed Housings
- **Damp Location**
- 5-Year Warranty

Applications:

LED retrofit trim have been designed to be a flexible lighting solution for retrofit and new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications

Other Models:

10W | 800LM | RDPF4-ADJ-MCT5
















Photometrics: RDPF6-ADJ-MCT5





35 30 25 20 15 10 2fc 1fc 0.5fc 0.1fc 0 5 10 15 20 25 30 35 Area 35'x 35' Mounting Height: 9'

BUG Rating: B1-U2-G0

BOG Rating. B I

Other Views:







Side View

Front View

Back View

Performance Table: RDPF6-ADJ-MCT5

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Ratin	LPW
RDPF6-ADJ-MCT5	11W	120V	880LM	2700K	B1-U2-G0	80
				3000K		
				3500K		
				4000K		
				5000K		

Sample Ordering

Model Lens Feature

Color Temp.

RDPF6 -

_ [

ADJ

MCT5

Accessory:

Blank = No Option For Accessories

E26-CONVERTER = SCREW-IN ADAPTER THAT FITS ANY STANDARD

Factory-Installed Option:

Blank = No Option For Accessories

OPT-EM-DL1EXT = EXTERNAL BATTERY BACKUP

ACCESSORY:



E26-CONVERTER

Includes Medium Base E-26 Screw-in Adapter That Fits Any Standard

FACTORY-INSTALLED OPTION:



OPT-EM-DL1EXT EXTERNAL BATTERY BACKUP

Example:

1. RDPF6-ADJ-MCT5

2. RDPF6-ADJ-MCT5 OPT-EM-DL1EXT (FOR RDLPF 11W MCT5 FIXTURE 120V)

 (FOR RDPF6 11W MCT5 FIXTURE 120V) (EXTERNAL BATTERY BACKUP)







Compatible Dimmer List:

MODEL NO.	BRAND	MODEL NO.	BRAND
LUXDM600-12 600W	ALMOND	S-600-IV 600W	LUTRON
SDM3/1000/WHTTE 1000W	АН	S-600-AL 600W	LUTRON
SDM/600/WHTTE 600W	AH	D-600R-IV 600W	LUTRON
18024 600W	GE	DV-603PH-WH 600W	LUTRON
6683 600W	LEVITON	S-603PH-WH 600W	LUTRON
6631-LA 600W	LEVITON	AY-600P-WH	LUTRON
LIGHT ALMOND NO.6672 600W	LEVITON	AYCL-153PH	LUTRON
603-6631-A 600W	LEVITON	SELV-300P-WH	LUTRON
6631-A 600W	LEVITON	DV-600P-WH	LUTRON
White/Lvory/Light Almond IPI10-1LZ 600W	LEVITON	SCL-153PH-WH	LUTRON
DV-603P600W	LUTRON	MACL-153MH-WH	LUTRON
S-600 600W	LUTRON	DVCL-253PH	LUTRON
DV-603PH-WH 600W	LUTRON	MSCL-OP153MH-WH	LUTRON
DV-600PH-WH 600W	LUTRON	MACL-153MLH-WH	LUTRON
S-603PGH-WH 600W	LUTRON	6683 600W	LEVITON
S-10PH 1000W	LUTRON	6631-LA 600W	LEVITON
D-600RH-DK 600W	LUTRON	LIGHT ALMOND NO.6672 600W	LEVITON
TG-600PH-WH 600W	LUTRON	603-6631-A 600W	LEVITON
SCL-153P-WH 600W	LUTRON	6631-A 600W	LEVITON
D-600R-WH 600W	LUTRON	White/Lvory/Light Almond IPI10-1LZ 600W	LEVITON



