



Type IC, Wet & Air-Tight

DESCRIPTION

4" Round Recessed LED With Integral Driver In Connection Box Fits Where No Other Recessed Fixture Can

FEATURES & BENEFITS

1/2" Deep - Install Directly Under Joists -Maximum Layout Flexibility

Driver Inside Connection Box - No Junction Box Needed


Fast & Easy To Install - Save On Labor

Type IC Rated - No Housing Required

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips. Ceiling Clearance Required For Driver: 2 1/2"

DIMENSIONS: ID 4" OD 4 7/8" Cut Out 4" to 4 1/4"



120V	TRIAC	: Dimmable	Э

Optional 120V - 347V

Driver Included

Driver 0-10V Dimmable





Order Separately as Cat # LLL-LD1535TB

AVAILABLE TRIMS





ORDERING GUIDE Example: LB4R / 30K / WH

	CCT	Trim Finish		
LB4R	1	/		c(V
3000K	30K	WH	White	E479
4100K	41K	вк	Black	
DTW 30-20K	32K	DTW is st	DTW is stocked in White Trim only and it is not Energy Star	

4" Round Economy Super Thin Recessed LED 11W

Project: Location: Cat #: Qty: Notes:

SPECIFICATION				
Applications	Recessed Ceiling, Showers & Soffits			
Energy Used	11 W			
Colour Temperature	3000 4100 Dim to Warm 3000K to 2000K			
Light Output	700 730 700			
Halogen Equivalent	65 W			
Beam Angle	110°			
CRI	80			
Default Driver Input	120V AC Triac Dimmable			
Optional Driver Input	120V-347V AC 0-10V Dimmable			
Junction Box Wire Capacity	Max 5 No 12 AWG or 8 No 14 AWG			
Power Factor	0.95			
Approved Location	Insulated Ceiling, Wet & Damp Locations			
IP Rating	IP 54			
Air Tight	Yes			
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)			
Projected Life	70% Light Output at 36,000 Hours			
Certification	cULus, Energy Star (30K and 41K only)			
Warranty	5 Year			

ACCESSORIES Sold Separately



Low Volage Extension Cables

10ft - cat # EXC10

Max 40 ft Allowed, FT4 / CMR rated



26" Flat Rough-In Plates - cat # RIP4



13" Flat Rough-In Plate - cat # MP4-2



13" Flanged Rough-In Plate - cat # MP4



Flanged Plate with Hanger Bars - cat # FRP4



Goof Ring OD 5 3/4" White - cat # GR4 Black - cat # GR4-BK

COMPLIANCE







Type IC Air-Tight

Lotus LED Lights USA

www.LotusLEDLights.com