



Tape Rope Hybrid

Features

- 2/3" LED spacing in white, perforated PVC housing
- Dimmable 5-100%*
- cETLus Listed, wet locations
- 3/8"W x 1/4"H
- 60,000 hours rated life
- Sold as case quantities of 6

Available Colors



3000K



Red

Dimming Options

- ELV (5-100%*)

Listing / Ratings

- Indoor/outdoor use

Technical Information

Series	120-TL60
Input Voltage	120V AC, 60Hz
CCT	3000K WW / GR / RE
CRI	82+ (WW)
Wattage	See individual product
Lumens	65Lm/ft (WW)
Max Run	106 feet
Cutttable	N/A
Dimmable	5-100%*
Rating	cETLus Listed, wet locations
Rated Life	35,000 hrs

*Minimum loads may apply. Per the NEC, switched wall outlets cannot be used with wall dimmers.

Ordering Information

120-TL60-3.3-WW	3.3ft 3000K Kit / 4.8W / 65Lm/ft / 82 CRI
120-TL60-13.2-WW	13.2ft 3000K Kit / 19.2W / 65Lm/ft / 82 CRI
120-TL60-3.3-RE	3.3ft Red Kit / 2.2W
120-TL60-6.6-RE	6.6ft Red Kit / 4.4W
120-TL60-13.2-RE	13.2ft Red Kit / 8.8W
120-TL60-19.7-RE	19.7ft Red Kit / 13.2W
120-TL60-32.8-RE	32.8ft Red Kit / 22W
120-TL60-45.9-RE	45.9ft Red Kit / 33W
120-TL-JUMP-3	3ft jumper/linking cable
120-TL-JUMP-6	6ft jumper/linking cable
120-TL-JUMP-15	15ft jumper/linking cable
120-TL-TRACK-4	4ft clear plastic mounting track

Each kit includes clear plastic mounting clips with screws (1 set per foot), (1) 5ft 120V AC removable power cord with 1.6A inverter and (1) removable end cap