



RSPV SERIES VALOX CORD GRIPS



VALOX® CORROSION-RESISTANCE & FDA-WASHDOWN APPROVED CORD GRIPS

Tuff-Seal™ Cord Grips made of Valox are cutting-edge, non-metallic connectors with excellent heat, chemical and corrosion resistance. This material provides high mechanical, thermal and electrical properties for stability and reliability. Rated for IP and NEMA compliance, Remke Valox cord grips are ideal for applications that require an environmental seal against dirt, dust, moisture, fumes and chemicals - and are also approved for FDA-washdowns.

Remke Valox Cord Grips feature a compression bushing made of high-quality, oil-resistant Neoprene rubber with an anti-friction washer made of nylon. RSPV cord grips are suitable for use both indoors & outdoors to prevent cable pullout and control arc of bend. Available options include

- Wire mesh attachments
- Straight-body style for 3/8", 1/2" and 3/4" conduit sizes
- 90-degree body for 1/2" and 3/4" conduit.

Valox connectors are commonly used in Automation, OEMs Maintenance and repair operations, food processing, wastewater treatment, Petro chemical, marine and shipboard, pulp and paper processing.

NOTES

CORD GRIP ACCESSORIES

Locknuts: add "-L" to any part number
O-Rings: add "-R" to any part number

SPECIAL CONFIGURATIONS

Special configurations and materials are available. Consult factory.

All wire mesh is stainless steel.

Dimension & certification information on pages 62 & 66 in Tuff-Seal Technical Reference.

Valox is registered trademark of GE Plastics

RSPV SERIES-STRAIGHT

COMPLETE ASSEMBLY PART NUMBERS

Conduit Size (NPT)	Cable Range	Cord Grip	Cord Grip With Mesh
3/8"	.125 - .188	RSPV-003	**
	.188 - .250	RSPV-004	RSPV-004-E
	.250 - .312	RSPV-005	RSPV-005-E
	.312 - .375	RSPV-006	RSPV-006-E
	.375 - .438	RSPV-007	RSPV-007-E
1/2"	.125 - .188	RSPV-103	**
	.188 - .250	RSPV-104	RSPV-104-E
	.250 - .312	RSPV-105	RSPV-105-E
	.312 - .375	RSPV-106	RSPV-106-E
	.375 - .438	RSPV-107	RSPV-107-E
	.438 - .500	RSPV-108	RSPV-108-E
	.500 - .562	RSPV-109	RSPV-109-E
	.562 - .625	RSPV-110	RSPV-110-E
3/4"	.438 - .500	RSPV-208	RSPV-208-E
	.500 - .562	RSPV-209	RSPV-209-E
	.562 - .625	RSPV-210	RSPV-210-E
	.562 - .688	RSPV-211	RSPV-211-E
	.625 - .750	RSPV-212	RSPV-212-E
	.688 - .812	RSPV-213	RSPV-213-E

**Contact Remke for mesh availability on this part number

RSPV SERIES-90°

COMPLETE ASSEMBLY PART NUMBERS

Conduit Size (NPT)	Cable Range	Cord Grip	Cord Grip With Mesh
1/2"	.125 - .188	RSPV-9103	**
	.188 - .250	RSPV-9104	RSPV-9104-E
	.250 - .312	RSPV-9105	RSPV-9105-E
	.312 - .375	RSPV-9106	RSPV-9106-E
	.375 - .438	RSPV-9107	RSPV-9107-E
	.438 - .500	RSPV-9108	RSPV-9108-E
	.500 - .562	RSPV-9109	RSPV-9109-E
	.562 - .625	RSPV-9110	RSPV-9110-E
3/4"	.438 - .500	RSPV-9208	RSPV-9208-E
	.500 - .562	RSPV-9209	RSPV-9209-E
	.562 - .625	RSPV-9210	RSPV-9210-E
	.562 - .688	RSPV-9211	RSPV-9211-E
	.625 - .750	RSPV-9212	RSPV-9212-E
	.688 - .812	RSPV-9213	RSPV-9213-E

*Cable may have to be stripped to pass through the bore of the body

**Contact Remke for mesh availability on this part number

